



TOP OPTIONS  
 1) LEAD ONLY  
 2) + SUPPORT ROPE  
 3) + EYE RING

PW ANODE - QUOTE REQUEST FORM

ELECTROLYTE \* (CIRCLE ONE)      SEAWATER      BRACKISH      FRESHWATER

ANODE CURRENT RATING (AMPS)      \_\_\_\_\_

ASSEMBLY DIAMETER (CIRCLE ONE)      2 INCH    3 INCH    OTHER \_\_\_\_\_

ANODE LENGTH (CIRCLE ONE)      4 FOOT    5 FOOT    1 METER    OTHER \_\_\_\_\_

TOP OPTIONS (CIRCLE ONE)      LEAD ONLY      SUPPORT ROPE      EYE RING

BOTTOM OPTIONS (CIRCLE ONE)      EYE RING      BOTTOM WEIGHT\*\*      \_\_\_\_\_ LBS.

ANODE LIFE : STANDARD IS 20-YRS. IF LONGER LIFE REQUIRED, PLEASE SPECIFY: \_\_\_\_\_ YRS.

\* if known, provide the conductivity or resistivity of the water where the anodes will be placed.  
 \*\* provide the desired weight requested and we will review and confirm the options available.

©2021 MATCOR, INC.

NOTES:  
 \* ANODE DIA. & LENGTH WILL DEPEND ON OPERATING CURRENT DENSITY & ELECTROLYTE (I.E. ANODE RESISTANCE).

REVISIONS					
NO.	DESCRIPTION	DATE	BY	CHK	APPR
A	ISSUED FOR COMMENTS	07/01/21	MRP	GWS	GWS



MATCOR PW™-ANODE Quote Request Dwg.

DRAWN BY: MRP	MATCOR INC. 101 LIBERTY LANE CHALFONT, PA 18914	PHONE: 215-348-2974 FAX: 215-348-2699
APPROVED BY: GWS	DWG NO. R-MAT-PW-ANODE-QRD1	
CREATION DATE: 07/01/21		
SCALE: NTS		